

PM1063N/PM1063P Specifications:

| Model | PM1063N | PM1063P |
|--------------------------------|---|----------------------|
| Signal System | NTSC | PAL |
| Scanning System | 2:1 Interlace | |
| Scanning Frequency(H) | 15.734kHz | 15.625kHz |
| Scanning Frequency(V) | 59.94Hz | 50Hz |
| Image Sensor | 1/4" IT CCD | |
| Sync. System | Internal | |
| Total Pixels Number | 811(H) x 508(V) 410K | 795(H) x 596(V) 470K |
| Effective Pixels Number | 768(H) x 494(V) 380K | 752(H) x 582(V) 440K |
| Horizontal Resolution | 500 TV Lines (Color), 570 TV Lines (BW) | |
| Video Output Level | 1.0Vp-p (75Ω, composite) | |
| S/N Ratio | More than 50dB (AGC Off) | |
| Digital Zoom Ratio | 10x | |
| Lens | 10x Optical Zoom (3.8 (W) mm ~ 38 (T) mm, F1.8) | |
| Min. Illumination | 0.7Lux (Color), 0.02Lux (BW), 50 IRE | |
| Day & Night System | Electronic sensitivity-up (DSS), ICR (AGC type) | |
| Digital Noise Reduction (SDNR) | Low / Middle / High / Off | |
| White Balance | Auto/Manual (Red, Blue Gain Adjustable) | |
| Digital Slow Shutter | Off/2FLD ~ 128 FLD Mode | |
| OSD Menu | Menu/PTZ Information | |
| Privacy Zone | ON/OFF (4 zone settings) | |

| | | |
|--------------------------|---|-------------------------|
| Electronic Shutter Speed | 1/60sec ~ 1/120,000 sec | 1/50sec ~ 1/120,000 sec |
| Preset | 127 positions with labels | |
| Swing | 8 swings | |
| Pattern | 4 patterns | |
| Group | 8 groups (max. 20 entries) | |
| Panning/Tilting Range | Pan: 345° Non-endless rotation; Tilt: 190° | |
| Panning/Tilting Speed | Manual: 1° ~ 360°/sec; Preset: 360°/sec; Swing: 1°~180°/sec | |
| Power Voltage | 12VDC | |
| Power Consumption | Max. 3.5W | |
| Dimensions | 130.2(W) x 130.5(D) x 142.1(H) mm | |
| Weight (Net) | Approx. 1kg | |