

S1965NX/S1965PX Specifications:

Model	S1965NX	S1965PX
Signal System	NTSC	PAL
Scanning System	2:1 Interlace	
Scanning Frequency(H)	15.734kHz	15.625kHz
Scanning Frequency(V)	59.94Hz	50Hz
Image Sensor	1/4" Exview CCD	
Sync. System	Internal/Line-Lock	
Total Pixels Number	811(H) x 508(V) 410K	795(H) x 596(V) 470K
Effective Pixels Number	768(H) x 494(V) 380K	752(H) x 582(V) 440K
Horizontal Resolution	530 TV Lines	
Video Output Level	1.0Vp-p (75Ω, composite)	
S/N Ratio	More than 50dB (AGC off)	
Min. Illumination	1.0lx (color), 0.07lx (color,DSS), 0.01lx (B/W,DSS) 50IRE	
White Balance	Auto/Manual(Red, Blue Gain Adjustable)	
OSD Menu	On/Off	
WDR (Wide Dynamic Range)	On/Off	
Privacy Zone	On/Off(8 zone settings)	
Electronic Shutter Speed	1/4~1/10,000sec	1/3~1/10,000sec
Preset	128 positions with labels	

Swing	8 swings
Pattern	4 patterns (about 5min/pattern)
Group	8 groups (max. 20 entries)
Panning/Tilting Range	Pan: 360° endless rotation; Tilt: 90°
Panning/Tilting Speed	Manual: 1° ~ 360°/sec; Preset: 360°/sec; Swing: 1°~180°/sec
Power Voltage	24VAC/2A
Power Consumption	48VA
Dimensions	Dome: 149(Φ); Housing: 163.6(Φ) x 230.9(H) mm (without decorative bottom ring)
Weight (Net)	Approx. [Main Body] 2.5kg, [Wall Mount] 768g, [Pendant Mount] 880g, [In-Ceiling] 984g